



IP56 Braided Extension Leads

FEATURES

- Available with either 10 Amp or 15 Amp
- 80% screen is EMC Compliant
- Tinned Copper Screen for Mechanical
- Tinned Copper Screen Earthed For Fault Protection
- Excellent Flexibility

PACKAGING

All leads already labeled with length & Part No

Product Code	Length	Cable Size mm2	Cable Amps	Plug & Socket Amps
BXLIP565M10A	5 MTR	1.5	15	10
BXLIP5610M10A	10 MTR	1.5	15	10
BXLIP5615M10A	15 MTR	1.5	15	10
BXLIP5620M10A	20 MTR	1.5	15	10
BXLIP5625M10A	25 MTR	2.5	25	10
BXLIP5630M10A	30 MTR	2.5	25	10
BXLIP565M15A	5 MTR	1.5	15	15
BXLIP5610M15A	10 MTR	1.5	15	15
BXLIP5615M15A	15 MTR	1.5	15	15
BXLIP5620M15A	20 MTR	1.5	15	15
BXLIP5625M15A	25 MTR	2.5	25	15
BXLIP5630M15A	30 MTR	2.5	25	15

Please Note:
Amperage ratings specified are in accordance with AS/NZS 3008.1.1.2009 Table 14 (Flexible "Spaced").

Please Note

Please consult with your Electrician / Engineer to ensure this cable is suitable for the intended application and installation.
Elcon Cables takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.

NSW (02) 9602 4888
salesnsw@elconcables.com.au
WA (08) 9358 1809
saleswa@elconcables.com.au

QLD (07) 3805 6455
salesqld@elconcables.com.au
SA/NT (08) 8326 4833
salessa@elconcables.com.au

VIC/TAS (03) 9558 1044
salesvic@elconcables.com.au