



Vinyl Bundling Tapes

HelaTape Duct13

Electricians Duct Tape is designed for bundling, holding, fixing and maintenance applications. It can be also used as temporary surface protection of steel and aluminium parts.

Features and benefits

- Vinyl film coated with high-quality rubber adhesive
- Excellent performance and durability
- Easy to tear
- Used for bundling, holding, fixing and maintenance
- Suitable for ducted air conditioning systems

More details: Click on article number in table.



HelaTape Duct13 – universal and very strong vinyl bundling tape.

MATERIAL	Polyvinylchloride (PVC)
Operating Temperature	0 °C to +80 °C
Tensile Strength	20 N/mm ²
Elongation at break (min.)	200 %
Adhesion to Steel	2.5 N/10 mm
Adhesion to Backing	2.5 N/10 mm
Dielectric Strength	40 kV/mm

RoHS ✓

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Pack Cont.	Local Part No.	Art.-No.
HTAPE-DUCT13	0.13	48.0	30.0 m	Grey (GY)	1 pc.	DUCT13	924-00963

All dimensions in mm. Subject to technical changes.

Technical data sheet

Article number:
924-00963

HTAPE-DUCT13

Product Group	Vinyl Bundling Tapes
Product Family	HelaTape Duct13
Material	Polyvinylchloride (PVC)
Colour	Grey (GY)
Adhesion to Backing	2.5 N/10 mm
Adhesion to Steel	2.5 N/10 mm
Breaking Strength	25 N/10 mm
Dielectric Strength	40 kV/mm
Elongation at break (min.)	200 %
Length (L)	30 m
Operating Temperature	0 °C to +80 °C
Package Content	1 pc.
Package Content packed in	reel
Tensile Strength	20 N/mm ²
Thickness (T)	0.13 mm
Width (W)	48 mm

RoHS 

RoHS EU Declaration of Conformity

Article number: 924-00963 – HTAPE-DUCT13-PVC-GY

We herewith declare, that the above mentioned article does in accordance with the European RoHS Directive 2011/65/EU and its amendment 2015/863/EU not contain the following substances in concentrations above the mentioned tolerations:

Restricted substances referred to in Article 4(1) and maximum concentration values tolerated by weight in homogeneous materials

- Lead (0.1 %)
- Mercury (0.1 %)
- Cadmium (0.01 %)
- Hexavalent chromium (0.1 %)
- Polybrominated biphenyls (PBB) (0.1 %)
- Polybrominated diphenyl ethers (PBDE) (0.1 %)
- Bis(2-ethylhexyl) phthalate (DEHP) (0.1 %)
- Butyl benzyl phthalate (BBP) (0.1 %)
- Dibutyl phthalate (DBP) (0.1 %)
- Diisobutyl phthalate (DIBP) (0.1 %)

This data sheet was issued by:

HellermannTyton Australia
Units 2, 12-14 Mangrove Lane,
Taren Point, NSW 2229
Phone: +61 2 9540 3955
cservice@HellermannTyton.com.au
www.HellermannTyton.com.au

Note: This confirmation corresponds to a manufacturer declaration in terms of the EU RoHS Directive, Article 4(1). Any alterations of the described product makes this declaration invalid.

A current version you find on web at HellermannTyton.com