

COPPER LUG TERMINATOR KIT - LARGE

This kit has large quantities of copper lugs and links from 2.5 to 16mm² and a tool for crimping (Part No. K26), all packed in a sturdy plastic box (Part No. KPB1).

CABAC copper crimp lugs are made from 99.9%+ cu high conductivity annealed copper which gives the best electrical properties possible. They are capable of withstanding a continuous operating temperature of 155° C, which is well above the temperature properties of most lugs.

It is our recommendation that CABAC copper crimp lugs should be crimped with standard Australian tooling.

FEATURES

- Kit contains a large quantities totalling 576 pieces of Uninsulated Copper lugs and links
- Lugs and links range from 2.5-16mm²
- Copper lug hand crimper tool K26 included
- Supplied with KPB1 plastic compartment box



KIT CONTENTS

PART NO.	QTY	PART NO.	QTY
CAL2.5-5	100	CAL16-6	25
CAL2.5-6	100	CAL16-8	25
CAL4-6	50	CAS2.5	100
CAL6-6	50	CAS6	50
CAL10-6	50	CAS16	25
K26	1	KPB1	1

ORDERING INFORMATION

PART NO.	DESCRIPTION
KPBK1	COPPER LUG TERMINATION KIT - LARGE

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

COMBINATION HAND CRIMPER 1.5-16MM²

FEATURES & BENEFITS

- Low cost ratchet crimper
- High leverage to create a 'W' crimp for a larger crimp range
- Ratchet operation ensures correct crimp
- Suitable for copper lugs and un-insulated terminals 1.5-16mm²



ORDERING INFORMATION

Part No.	Description
K26	COMBINATION HAND CRIMPER 1.5-16MM ²

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.