



Ring Terminals

Single Grip Pre-Insulated

Single grip ring terminals provide a dependable solution for wire-to-stud connections in general-purpose installations with low to moderate vibration. The ring design ensures consistent contact, while the PVC insulation supports strain relief and electrical protection. Use with the HYYT1 crimping tool for best results.


Features and benefits

- Three conductor sizes for versatile wiring needs
- Colour coded for easier identification
- Recommended for general purpose electrical installations
- Packaged in resealable bag
- REACH compliant



Ring Terminal, 1R series.

More details: Click on article number in table.



Ring Terminal, Front View

Ring Terminal, Side View



Ring terminal, 2R series.



Ring terminal, 3R series.

MATERIAL	Copper (CU), Polyvinylchloride (PVC)
Operating Temperature	+75 °C
Max Voltage	600 V

RoHS

TYPE	Drawing	Conductor Size Range (mm ²)	Hole Ø (FH)	Width (W)	Length (L)	Length (L2)	Length (L3)	Ø (D)	Max Current	Colour	Pack Cont.	Tools	Art.- No.
1R3		0.5-1.5	3.2	5.5	17.0	10	7.0	4.3	19 A	Red (RD)	100 pcs.	60	924-00515
1R4		0.5-1.5	4.3	8.0	21.2	10	11.2	4.3	19 A	Red (RD)	100 pcs.	60	924-00516
1R5		0.5-1.5	5.3	8.0	21.2	10	11.2	4.3	19 A	Red (RD)	100 pcs.	60	924-00517
1R6		0.5-1.5	6.4	11.6	27.1	10	17.1	4.3	19 A	Red (RD)	100 pcs.	60	924-00518
1R8		0.5-1.5	8.4	11.6	27.1	10	17.1	4.3	19 A	Red (RD)	100 pcs.	60	924-00519
1R10		0.5-1.5	10.5	13.7	31.0	10	21.0	4.3	19 A	Red (RD)	100 pcs.	60	924-00520
1R12		0.5-1.5	13.0	19.0	34.5	10	24.5	4.3	19 A	Red (RD)	100 pcs.	60	924-00521
2R3		1.5-2.5	3.2	8.5	22.5	10.7	11.8	4.7	27 A	Blue (BU)	100 pcs.	60	924-00522
2R4		1.5-2.5	4.3	8.5	22.5	10.7	11.8	4.7	27 A	Blue (BU)	100 pcs.	60	924-00523
2R5		1.5-2.5	5.3	9.5	22.5	10.7	11.8	4.7	27 A	Blue (BU)	100 pcs.	60	924-00524
2R6		1.5-2.5	6.4	12.0	27.6	10.7	16.9	4.7	27 A	Blue (BU)	50 pcs.	60	924-00525
2R8		1.5-2.5	8.4	12.0	27.6	10.7	16.9	4.7	27 A	Blue (BU)	50 pcs.	60	924-00526
2R10		1.5-2.5	10.5	13.7	31.4	10.7	20.7	4.7	27 A	Blue (BU)	50 pcs.	60	924-00527
2R12		1.5-2.5	13.0	19.0	35.0	10.7	24.3	4.7	27 A	Blue (BU)	50 pcs.	60	924-00528

Recommended Tools: 60=HYYT1. For more information on toolings please go to www.HellermannTyton.com.au/application-tooling.

All dimensions in mm. Tolerance ± 2%. Subject to technical changes.



TYPE	Drawing	Conductor Size Range (mm ²)	Hole Ø (FH)	Width (W)	Length (L)	Length (L2)	Length (L3)	Ø (D)	Max Current	Colour	Pack Cont.	Tools	Art.-No.
3R3		4.0-6.0	3.2	9.5	26.2	13.6	12.6	6.7	48 A	Yellow (YE)	100 pcs.	60	924-00529
3R4		4.0-6.0	4.3	9.5	26.2	13.6	12.6	6.7	48 A	Yellow (YE)	50 pcs.	60	924-00530
3R5		4.0-6.0	5.3	9.5	26.2	13.6	12.6	6.7	48 A	Yellow (YE)	50 pcs.	60	924-00531
3R6		4.0-6.0	6.4	12.0	32.2	13.6	18.6	6.7	48 A	Yellow (YE)	50 pcs.	60	924-00532
3R8		4.0-6.0	8.4	15.0	34.4	13.6	20.8	6.7	48 A	Yellow (YE)	50 pcs.	60	924-00533
3R10		4.0-6.0	10.5	15.0	34.4	13.6	20.8	6.7	48 A	Yellow (YE)	50 pcs.	60	924-00534
3R12		4.0-6.0	13.0	19.2	39.1	13.6	25.5	6.7	48 A	Yellow (YE)	50 pcs.	60	924-00535

Recommended Tools: 60=HYT1. For more information on toolings please go to www.HellermannTyton.com.au/application-tooling.

All dimensions in mm. Tolerance ± 2%. Subject to technical changes.