

TPS Flats – Twin + Twin and Earth

Electra Cables' Flat TPS Twin & Earth and Twin cable ranges are trusted throughout Australia and New Zealand, known for their high quality, durability, and ease of use. Supplied on the iconic blue drums, these cables are designed to perform reliably across a wide range of installation environments and climatic conditions.

Electra Cables is one of Australasia's largest stockists, providing dependable access to Flat TPS cable products when and where they are needed.

Conductor:	Plain Annealed Copper
Insulation:	V-90 PVC
Voltage:	450/750V
Standards:	AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808
Certification:	E.E.S.S. (Electrical Equipment Safety Scheme) Responsible Supplier - E.R.A.C. (Electrical Regulatory Authorities Council)
Greenstar:	Approved and Certified under Pathway 2 + Extra Credit
Vinyl Council:	Endorsed and Approved

Twin and Earth (2C+E)

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	SHEATH Colours Available	O.D.
SRF3010V	1	2C+E	0.6	0.9	White	9.0 x 4.2
SRF3015V	1.5	2C+E	0.6	0.9	White / Black / Grey / Red Trace	10.0 x 4.6
SRF3025V	2.5	2C+E	0.7	1	White / Black / Grey / Red-Trace	12.4 x 5.5
SRF3040V	4	2C+E	0.8	1.1	White / Black / Grey	14.0 x 6.5
SRF3060V	6	2C+E	0.8	1.1	White / Black / Grey	15.2 x 7.1
SRF3100V	10	2C+E	1	1.2	White	18.9 x 8.6
SRF3160V	16	2C+E	1	1.3	White	21.8 x 9.9

*Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm. Also see LSZH, AC, HT, Non-Migratory variations.

3C+E Flat

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	SHEATH Colours available	O.D.
SRF4015V	1	3C+E	0.6	0.9	White	12.6 x 4.6
SRF4025V	1.5	3C+E	0.7	1	White	15.8 x 5.5

*Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm.

Twin and Twin Active

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	SHEATH Colours Available	O.D.
SRF2010V	1	Red / Black	0.6	0.9	White	6.5 x 4.2
SRF2010AV	1	Red / White	0.6	0.9	White	6.5 x 4.2
SRF2015V	1.5	Red / Black	0.6	0.9	White	7.2 x 4.6
SRF2015AV	1.5	Red / White	0.6	0.9	White / Black	7.2 x 4.6
SRF2025V	2.5	Red / Black	0.7	1	White / Black	8.9 x 5.5
SRF2025AV	2.5	Red / White	0.7	1	White	8.9 x 5.5
SRF2040V	4	Red / Black	0.8	1.1	White / Black	10.6 x 6.5
SRF2040AV	4	Red / White	0.8	1.1	White	10.6 x 6.5
SRF2060V	6	Red / Black	0.8	1.1	White	11.7 x 7.1
XSRF2060V**	6	Red / Black	0.8	1.1	Orange	11.7 x 7.1
SRF2060AV	6	Red / White	0.8	1.1	White	11.7 x 7.1
SRF2100V	10	Red / Black	1	1.2	White	14.6 x 8.6
XSRF2100V**	10	Red / Black	1	1.2	Orange	14.6 x 8.6
SRF2160V	16	Red / Black	1	1.3	White	16.9 x 9.9
XSRF2160V**	16	Red / Black	1	1.3	Orange	16.9 x 9.9

*Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm. **Available in WA only

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38